Rec'd PCT/PTO 17 JUN 2005
(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

## (19) World Intellectual Property Organization International Bureau



## 

(43) International Publication Date 8 July 2004 (08.07.2004)

**PCT** 

## (10) International Publication Number WO 2004/056717 A1

(51) International Patent Classification7:

C03C

(21) International Application Number:

PCT/US2003/040587

(22) International Filing Date:

18 December 2003 (18.12.2003)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

0229447.8

18 December 2002 (18.12.2002) GI

1) Applicant (for all designated States except US)


- (71) Applicant (for all designated States except US):
  ARADIGM CORPORATION [US/US]; 3929 Point Eden Way, Hayward, CA 94545 (US).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): KING, Toby [GB/US]; 1176 Palo Alto Avenue, Palo Alto, CA 94301

(US). BRIDGES, Paul [GB/US]; 932 Boyce Avenue, Palo Alto, CA 94301 (US). SHERGOLD, Oliver [GB/GB]; 51 High Street, Cottenham, Cambridgeshire CB4 8SA (GB).

- (74) Agent: BOZICEVIC, Karl; BOZICEVIC, FIELD & FRANCIS LLP, 200 Middlefield Road, Suite 200, Menlo Park, CA 94025 (US).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: A METHOD OF PROOF TESTING GLASS



(57) Abstract: A method of proof testing glass containers is disclosed. The method involves applying pressure to a sealed container in two discrete stages as shown in figure 1. In the first stage, the pressure is increased to a peak over at a first rate. In the second stage, the pressure is reduced to zero at a much greater rate.